



1485C KwikLink Cable	1485P KwikLink General Purpose Connectors	1485P KwikLink Connectors	1485T & 1485P Pigtail KwikLink Connectors
			
<ul style="list-style-type: none"> Keyed flat trunk cable for use with Insulation Displacement Connectors (IDCs) 	<ul style="list-style-type: none"> Vampire connectors for use with KwikLink flat cable in general purpose applications IP67 	<ul style="list-style-type: none"> Insulation Displacement Connectors (IDCs) for use with KwikLink flat cable Sealed: NEMA 6 & 13; IP67; 1200 psi washdown Unsealed: NEMA 1; IP60 	<ul style="list-style-type: none"> Insulation Displacement Connector with integral class 1 round cable pigtail for interfacing a device or power supply to flat cable Sealed: NEMA 6 & 13; IP67; 1200 psi washdown Unsealed: NEMA 1, IP60
<ul style="list-style-type: none"> N/A 	<ul style="list-style-type: none"> Micro QD 	<ul style="list-style-type: none"> Micro Open-style Terminator 	<ul style="list-style-type: none"> Mini QD Conductor
<ul style="list-style-type: none"> Keyed to prevent wiring mishaps TPE or PVC jacket Class 1 or class 2 rated cable versions Available in spools up to 420m 	<ul style="list-style-type: none"> Plug and play installation Two-piece housing Designed for general purpose applications 	<ul style="list-style-type: none"> UL listed and CSA certified Valox construction Plug and play installation 	<ul style="list-style-type: none"> Plug and play installation Allows Class 1 drop to KwikLink system Includes IDC connector and pigtail module
<ul style="list-style-type: none"> M115 catalog pages 6-6, 6-12 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-7 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-14 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-15 www.ab.com/catalogs

Description/Features

Connections

Extra Features

Additional Info

1485P KwikLink Splice Kits	1485K KwikLink Drop Cables	1485C Thick Media	1485R & 1485G Thin Media
			
<ul style="list-style-type: none"> A pair of Insulation Displacement Connectors factory-joined with Class 1 round cable for splicing together two sections of a flat cable network Sealed: NEMA 6 & 13; IP67; 1200 psi washdown Unsealed: NEMA 1, IP60 	<ul style="list-style-type: none"> 4-wire unshielded drop cables for use exclusively with KwikLink systems 	<ul style="list-style-type: none"> 1/2" (12.2mm) cable for DeviceNet trunkline 	<ul style="list-style-type: none"> 1/4" (6.9mm) cable for DeviceNet trunkline or droplines
<ul style="list-style-type: none"> KwikLink module to KwikLink module 	<ul style="list-style-type: none"> Mini QD Micro QD Conductor 	<ul style="list-style-type: none"> Mini QD Conductor Field attachable connectors Terminators Cable spools Panel-mount receptacles 	<ul style="list-style-type: none"> Mini QD Micro QD Conductor Field attachable connectors Terminators Cable spools Panel-mount receptacles
<ul style="list-style-type: none"> Plug and play installation Available in standard splice kit and power isolation splice kit versions Includes IDC connectors, splice module and flat cable end caps 	<ul style="list-style-type: none"> For use only with KwikLink Flat Media system Epoxy coated coupling nut PVC jacket 	<ul style="list-style-type: none"> PVC jacket Standard cordset lengths up to 30m Available in raw spools up to 500m 	<ul style="list-style-type: none"> Yellow TPE or gray PVC jacket Standard cordset lengths up to 6m Available in raw spools up to 600m
<ul style="list-style-type: none"> M115 catalog page 6-13 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog pages 6-8 and 6-17 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-20 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-21 www.ab.com/catalogs

Description/Features

Connections

Extra Features

Additional Info

	1485A Bulkhead Pass-Through Connectors	1485T PowerTap	1485P DeviceBox	1485P DevicePort
				
Description/ Features	<ul style="list-style-type: none"> Mini or micro bulkhead pass-through connectors for convenient routing of DeviceNet wiring through panel walls IP67 	<ul style="list-style-type: none"> Passive coupling device used to limit trunk current NEMA 3, 4X, 6P, 12 & 13; IP67; 1200 psi washdown 	<ul style="list-style-type: none"> Passive sealed junction boxes for up to 8 smart devices NEMA 3, 4X, 6P, 12 & 13; IP67; 1200 psi washdown 	<ul style="list-style-type: none"> Passive multi-port tap for up to 8 smart devices NEMA 4, 6P; IP67; 1200 psi washdown
Connections	<ul style="list-style-type: none"> Mini QD Micro QD 	<ul style="list-style-type: none"> Cage-clamp terminal strips 	<ul style="list-style-type: none"> Cage-clamp terminal strips 	<ul style="list-style-type: none"> Mini QD Micro QD
Extra Features	<ul style="list-style-type: none"> Nickel-plated brass housing standard Stainless steel housing versions available 	<ul style="list-style-type: none"> Allows for multiple power supplies 7.5A or 3.0A fuse protection (2x) Thick media and thin media versions 	<ul style="list-style-type: none"> 2, 4, or 8 ports Cord grip openings Direct connection to trunk Thick media and thin media versions 	<ul style="list-style-type: none"> 4 or 8 ports Connection to trunk via drop line
Additional Info	<ul style="list-style-type: none"> M115 catalog page 6-28 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-33 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-34 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog pages 6-16 and 6-35 www.ab.com/catalogs

	1485P T-Port	889N Auxiliary Power Media	898N Auxiliary Power/ Single Channel Safety Media
			
Description/ Features	<ul style="list-style-type: none"> Connects a single drop line to the trunk NEMA 4X, 6P, 12 & 13; IP67; 1200 psi washdown 	<ul style="list-style-type: none"> 4-pin patchcords, receptacles, T-ports, terminal chambers, bulkhead pass-through connectors and accessories for auxiliary power for DeviceNet 	<ul style="list-style-type: none"> 4-pin T-ports and shorting plugs wired to provide both auxiliary power and a single channel safety circuit <p>NOTE: safety circuit is passive and not part of the DeviceNet communication network.</p>
Connections	<ul style="list-style-type: none"> Mini QD Micro QD 	<ul style="list-style-type: none"> Mini QD Micro QD 	<ul style="list-style-type: none"> Mini QD
Extra Features	<ul style="list-style-type: none"> Right or left keyway for positioning purposes on mini QD versions 	<ul style="list-style-type: none"> Yellow PVC jacket Standard patchcord lengths up to 30m 	<ul style="list-style-type: none"> Red PBT housing Male or female shorting plugs available For use in conjunction with standard auxiliary power media components
Additional Info	<ul style="list-style-type: none"> M115 catalog page 6-30 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-37 www.ab.com/catalogs 	<ul style="list-style-type: none"> M115 catalog page 6-40 www.ab.com/catalogs