



- NOTES:
- < 1 TO REGULATOR THRU POWER I/F PC BOARD.
 - < 2 CONTACTS ON RELAY RECTIFIER PC BOARD.
 - < 3 REMOVE JUMPER WHEN DB OPTION USED.
 - < 4 FOR NOTE, SEE SHEET 10.
 - < 6 FOR NOTE, SEE SHEET 3.
 - < 7 FOR NOTE, SEE SHEET 3.
 - < 8 OPTIONAL KIT - SEPARATELY MOUNTED.
 - < 16 FOR DETAILS, SEE TABLE ON SHEET 3.
 - < 18 FOR S6 DRIVES, THE A1 CONNECTION TO 16FU IS REPLACED BY A JUMPER BETWEEN 47(+) AND A1 ON THE POWER I/F BOARD.
 - < 19 OPTIONAL KIT - MOUNTED IN/ON DRIVE.

SCHMATIC FOR
100 THRU 150HP AT 230VAC
200 THRU 300HP AT 460VAC

- ⊠ FASTON CONNECTOR
- TP TWISTED PAIR
- PX-X PLUG TERMINAL CONNECTION
- TERMINAL CONNECTION

11	-02 C/R 357687	C/R 357687
10	-01 N/R 500369	DATE 1-9-98
9	-01 N/R 500369	SEE C/R
8	-01 N/R 500369	REV -03
7	-01 N/R 500369	C/R 357637
6	-01 N/R 500369	DATE 9/12/97
5	-02 C/R 357637	SEE C/R
4	-02 C/R 357687	REV -02
3	-02 C/R 357637	N/R 500369
2	-01 N/R 500369	DATE 3/14/97
SHEET	REV STATUS	SEE N/R BODY

RELIANCE ELECTRIC
RELIANCE ELECTRIC INDUSTRIAL COMPANY • CLEVELAND, OH 44117

WIRING DIAGRAM BULLETIN 1397
S6/S6R 150/300HP 230/460VAC

DR. DCS	DATE 3-4-97	SCALE: 1=1
CK. TJS	ENG'R JB-MQ	SHEET 1 OF 11
APP. TMC	DISTRIBUTION 13-688-76	WD 30373-23