



MOUNTING HOLE LOCATIONS

- NOTES:
 1. RECOMMENDED HOLE SIZE FOR MOUNTING FASTENER, $\varnothing 3.5\text{mm}$ [1.38"]
 2. DEBURR FASTENER HOLE.

OPEN DRIVE

TYPE 1 DRIVE WITH CONDUIT PLATE

PARTS MUST CONFORM TO APPLICABLE ROCKWELL AUTOMATION MANUFACTURING STANDARDS
 CAD DOCUMENT
 FILE NAME: 357120-6

REFERENCES		OUTLINE DRAWING		CONFIDENTIAL AND PROPRIETARY INFORMATION	
REVISION	EMBRACING APPLY BEFORE SURFACE TREATMENT	FRAME 2	DATE	THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE REPRODUCED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.	
AUTHORIZATION	EMBRACING IN MILLIMETERS	POWERFLEX 753 & 755	DATE	AUTOMATION, INC. AND MAY NOT BE REPRODUCED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.	
	TOLERANCES UNLESS OTHERWISE SPECIFIED:	Rockwell Automation	DATE	AUTOMATION, INC. AND MAY NOT BE REPRODUCED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.	
	.X:± N/A		DATE	SHEET	2 OF 4
03	1033405 .XX:± N/A	DR. K.KALWARDT	06-19-07	DWG.	357120-6
02	1031783 ANGLES:± N/A	CHKD. K.KALWARDT	09-20-07	SIZE	
01	1028532	APPD. J.BRUBAKER	09-20-07		